Electric mountain bike MONDRAKER-Prime 29 (SPE), black-racing silver



Available sizesReference numberEan numberQuantityM / 29"75894084353928559381 ks

Suggested retail price: 4099 € s DPH

Description

Mondraker electric mountain bike. The Bosch Performance Line CX Cruise GEN4 motor offers ideal assistance when cycling. Mondraker has adapted the Forward geometry to offer you an unlimited way to spend many hours on the bike.

Comfort and lightness are the most important characteristics, so you can enjoy the Prime 29 electric bike on any terrain. RockShox Recon Silver RL fork with 120 mm travel ensures comfort. Ebike Mondraker is one of the top electric bikes. E-bike is a great companion for cycling tours. When choosing the right size, it is also suitable as a ladies' electric bike or an electric bike for seniors.

Technical parameters

Frame	Prime Xtralite 6061 Full Butted Alloy, Forward Geometry, internal removable battery, tapered head tube, Boost 12x148mm rear axle, integrated dropout speed sensor
Fork	RockShox Recon Silver RL 29, 120mm, Motion control, Solo Air, tapered steerer tube, Boost 15x110mm axle, 42mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload
Transfers	
Derailleur	Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1
Front brake	Sram Level TL, 2 piece caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pad
Rear brake	Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
Brake levers	Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings

Shifting Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click

Cranks

Race Face Aeffect ebike, 165mm

Chain

Sram SX Eagle, 12s, Powerlock

Cassette

Sram PG-1210, 11-50T, 12s

Front hub Formula DC711, Boost 15x110mm, sealed bearings, IS 6

bolts

Rear hub Formula EHL148 Boost 12x148mm, sealed bearings, IS 6

bolts

Maxxis Rekon 29x2.6, tubeless ready, dual compound,
EXO protection, 60TPI, folding bead, Maxxis Rekon
29x2.6, tubeless ready, dual compound, EXO protection,

60TPI, folding bead

Rims MDK-HP1 29, 30mm internal width, tubeless ready, 32

spokes

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, Width: 800mm, 9º backsweep, 5º upsweep, 31.8mm

barbore

Representative Onoff Sulfur FG 30mm 0º, 6061 forged alloy, 31.8mm

barbore

Seat post Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter

31.6mm, length 400mm

Saddle FIZIK Terra Aidon X5 145 mm

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB

sealed bearings, top 41x30.2x7x45°2x45°, bottom

51.9x40x8x45ºx45º

Converter Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

Foot for the derailleur Mondraker M068

Motor + battery

Bosch Performance Line CX Cruise (25Km/h) GEN4,

Bosch Powertube 625Wh, Bosch Purion

The weight of the bike 22.2 kg

Note: Mondraker warranty conditions

Head composition