

Electric mountain bike MONDRAKER-Prime R, cherry red-black



Available sizes	Reference number	Ean number	Quantity
M / 29"	758926	8435392849234	1 ks
XL / 29"	758928	8435392849258	1 ks

Suggested retail price: 4599 € s DPH

Description

Mondraker electric mountain bike. The Prime R electric mountain bike has a durable Prime Xtralite 6061 Full Butted Alloy aluminum frame with Forward Geometry . The bicycle is an ideal companion for cycling trips through the forest.

Ebike Monfraker also meets demanding criteria for technical parameters. The Mondraker e-bike belongs to the top electric bikes in its segment.

Technical parameters

Frame	Prime Xtralite 6061 Full Butted Alloy, Forward Geometry, internal removable battery, tapered head tube, Boost 12x148mm rear axle, integrated dropout speed sensor
Fork	RockShox 35 Silver TK 29, 120mm, TurnKey, Solo Air, tapered steerer tube, Boost 15x110mm axle, 35mm steel stanchions, 44mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload
Transfers	12
Derailleur	Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1
Front brake	Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
Rear brake	Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
Brake levers	Sram G2 R, tool-free reach adjust
Shifting	Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click

Cranks	Race Face Aeffect ebike, 165mm
Chain	Sram SX Eagle, 12s, Powerlock
Cassette	Sram PG-1210, 11-50T, 12s
Front hub	Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts
Rear hub	Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts
Coats	Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
Rims	MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes
Handlebars	Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm bar bore
Representative	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
Seat post	Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm
Saddle	FIZIK Terra Aidon X5 145mm
Head composition	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
Converter	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
Foot for the derailleur	Mondraker M068
Flu	Onoff Diamond, 1lock-on, 135mm
Motor + battery	Bosch Performance Line CX Cruise (25Km/h) GEN4 BS, Bosch Powertube 750Wh, Bosch Kiox 300

Note: [Mondraker warranty conditions](#)