

## Electric mountain bike MONDRAKER-Chaser 750, cherry red-black



Available sizes	Reference number	Ean number	Quantity
L / 29"	758914	8435392850308	1 ks

**Suggested retail price:** 5999 € s DPH

### Description

Mondraker electric mountain bike. The electric mountain bike has a Chaser 6061 Alloy Stealth Evo aluminum frame. The mountain ebike not only has a professional design, but also modern e-Bike Optimized Zero Suspension System and Forward Geometry technologies. A plus is the powerful motor and battery Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3, Bosch Powertube 750Wh, Bosch Kiox 300.

The mountain e-bike in red and black design will be your reliable companion on cycling trips. When choosing the right size, it is also suitable as a ladies' electric bike or an electric bike for seniors.

### Technical parameters

Frame	Chaser 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers, shock mudguard
Fork	Fox 36 29 Float FIT GRIP EVOL Rythm, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: sweep adjust compression, Low-speed rebound, air preload
Transfers	
Derailleur	Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1
Front brake	Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

Rear brake	Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
Brake levers	Sram G2 R, tool-free reach adjust
Shifting	Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click
Cranks	Race Face Aeffect ebike, 165mm
Chain	Sram SX Eagle, 12s, Powerlock
Cassette	Sram PG-1210, 11-50T, 12s
Front hub	Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts
Rear hub	Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts
Coats	Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
Rims	MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes
Handlebars	Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm bar bore
Representative	Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm bar bore
Seat post	Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm
Saddle	FIZIK Terra Aidon X5 145mm
Head composition	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
Converter	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
Foot for the derailleur	Mondraker M068
Motor + battery	Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3, Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3, Bosch Powertube 750Wh, Bosch Kiox 300
Silencer	RockShox Deluxe Select R Debonair, 205x65mm. Settings: Low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
Maximum range	-
The weight of the bike	24.8 Kg

**Note:** [Mondraker warranty conditions](#)