

Electric mountain bike MONDRAKER-Chaser R, marlin blue-black



Available sizes	Reference number	Ean number	Quantity
-----------------	------------------	------------	----------

Suggested retail price: 6199 € s DPH

Description

Mondraker electric mountain bike. The Chaser electric mountain bike has a durable Chaser 6061 Alloy Stealth Evo aluminum frame with the Optimized Zero Suspension System. The bicycle is an ideal companion for cycling trips through the forest.

Ebike Mondraker also meets demanding criteria for technical parameters. The Mondraker e-bike belongs to the top electric bikes in its segment.

Technical parameters

Frame	Chaser 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers, shock mudguard
Fork	Fox 36 29 Float FIT GRIP EVOL Rythm, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: sweep adjust compression, Low-speed rebound, air preload
Transfers	12
Dérailleur	Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
Front brake	Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
Rear brake	Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
Brake levers	Sram G2 R, tool-free reach adjust

Shifting	Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click
Cranks	Race Face Aeffect ebike, 165mm
Chain	Sram SX Eagle, 12s, Powerlock
Cassette	Sram PG-1210, 11-50T, 12s
Front hub	Mavic, Boost 15x110mm, IS 6 bolts
Rear hub	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts
Coats	Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
Rims	Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes
Handlebars	Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
Representative	Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
Seat post	Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm
Saddle	FIZIK Terra Aidon X5 145mm
Head composition	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
Converter	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
Foot for the derailleur	Mondraker M068
Silencer	Fox Float DPS Performance, 205x65mm. Settings: Compression 3 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
Motor + battery	Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3, Bosch Powertube 750Wh, Bosch Kiox 300

Note: [Mondraker warranty conditions](#)