

Electric mountain bike MONDRAKER-Crafty R, nimbus grey/black



Available sizes	Reference number	Ean number	Quantity
S / 29"	784632	8435392860093	1 ks
M / 29"	784633	8435392860109	3+
L / 29"	784634	8435392860116	3+
XL / 29"	784635	8435392860123	2 ks

Suggested retail price: 6799 € s DPH

Description

Mondraker electric mountain bike. The ZERO suspension system provides extremely flexible suspension and at the same time does not waste energy. The e-bike is really agile on trails, which is very necessary in an eMTB. It all adds up to maximum fun. The electric bike comes with a Bosch Performance CX Line Smart Control motor, a brand new Mini remote control and an integrated system controller.

Technical parameters

Frame	Crafty 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.
Fork	Fox 38 29 Float FIT GRIP EVOL Performance, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro-adjust compression, low-speed rebound, air preload
Transfers	
Dérailleur	Sram GX Eagle, Type 3 Roller Bearing Clutch, Cage Lock, 1x12s, X-Actuation 1:1
Front brake	Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

Rear brake	Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
Brake levers	Sram DB8, tool-free reach adjust
Shifting	
Cranks	Race Face Aeffect ebike, 165mm
Chain	Sram SX Eagle, 12s, Powerlock
Cassette	Sram PG-1210, 11-50T, 12s
Front hub	Mavic, Boost 15x110mm, IS 6 bolts
Rear hub	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts
Coats	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead, Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
Rims	Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes
Handlebars	Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
Representative	Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
Seat post	Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm
Saddle	FIZIK Terra Aidon X5 145mm
Head composition	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
Wires	Mavic J-bend double butted, contactless lacing
Converter	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
Foot for the derailleur	Mondraker M068
Engine and battery	Bosch Performance Line CX Cruise (25Km/h) Smart System, Bosch Powertube 750Wh, Bosch Kiox 300 / Bosch Mini Remote / Bosch System Controller
Damper setting	medium compression, medium rebound, air volume spacer 0.2
Silencer	Fox Float-X LV Performance, 205x65mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
Flu	Onoff Desert, 1lock-on, 135mm

Note: [Mondraker warranty conditions](#)